



US 20170048733A1

(19) **United States**(12) **Patent Application Publication**
Dalsgaard et al.(10) **Pub. No.: US 2017/0048733 A1**(43) **Pub. Date: Feb. 16, 2017**(54) **MINIMUM MEASUREMENT
REQUIREMENTS FOR MULTI-BROADCAST
SINGLE-FREQUENCY NETWORK
MEASUREMENTS****Publication Classification**

(51) **Int. Cl.**
H04W 24/08 (2006.01)
H04W 24/02 (2006.01)
H04W 76/04 (2006.01)
H04W 72/00 (2006.01)

(52) **U.S. Cl.**
CPC *H04W 24/08* (2013.01); *H04W 72/005*
(2013.01); *H04W 24/02* (2013.01); *H04W*
76/048 (2013.01); *H04W 88/02* (2013.01)

(71) Applicant: **Nokia Technologies Oy**, Espoo (FI)(72) Inventors: **Lars Dalsgaard**, Oulu (FI); **Ilkka
Keskitalo**, Oulu (FI)(73) Assignee: **Nokia Technologies Oy**, Espoo (FI)(21) Appl. No.: **15/306,440**(22) PCT Filed: **May 6, 2015**(86) PCT No.: **PCT/FI2015/050306**

§ 371 (c)(1),

(2) Date: **Oct. 24, 2016****Related U.S. Application Data**(60) Provisional application No. 61/990,993, filed on May
9, 2014.(57) **ABSTRACT**

Various communication systems may benefit from well-defined measurement requirements. For example, measurements for multi-broadcast single-frequency networks (MB-SFNs) may benefit from definition of minimum measurement requirements related to, for example, reference signal received power (RSRP) and reference signal received quality (RSRQ). A method may include obtaining MBMS configuration parameters. The method may also include defining generic minimum MBSFN measurement performance requirements, based on the MBMS configuration parameters.

